

SDC91 SPECIFICATION

FUNCTION	RANGE	RESOLUTION	ACCURACY	IMPEDEANCE
DC V	4 V	0.001 V	0.75% + 3 digits	Approx. 10M
	400 V	0.1 V		
AC V	400 V	0.1 V	1.2 % + 3 digits (451Hz - 4501Hz)	Approx. 10M
	600 V	1 V		
AC A	40 A	0.01 A	1.5 % + 5 digits (451Hz - 4501Hz)	
	400 A	0.1 A		
	700 A	1 A		
OHM	4 K Ω	0.001 K Ω	1 % + 3 digits	Protection 600V DC or Peak AC
CONTINUITY	4 K Ω	0.001 K Ω	< 110 digits	

GENERAL SPECIFICATIONS

- Display : 3 3/4 Digits LCD Display (4000 Counts)
: 2 times per second update
- Peak hold for all range
- Data hold for all range
- Continuity buzzer on 4k ohm range
- Indication Peak hold, Data hold, Low battery on LCD display
- Max. Volt. between any input and Ground : 600 V
- Operating Temp : 0 $^{\circ}$ C to 45 $^{\circ}$ C (32 $^{\circ}$ F to 113 $^{\circ}$ F)
- Storage Temp : -10 $^{\circ}$ C to 55 $^{\circ}$ C (14 $^{\circ}$ F to 131 $^{\circ}$ F)
- Relative Humidity : 0% to 80% (0 $^{\circ}$ C - 35 $^{\circ}$ C / 32 $^{\circ}$ F - 95 $^{\circ}$ F)
0% to 70% (35 $^{\circ}$ C - 50 $^{\circ}$ C / 95 $^{\circ}$ F - 122 $^{\circ}$ F)
- Power Supply : 9 Volt Battery
- Battery Life : 80 hrs. Alkaline
- Size (H X L X W) : 40 mm X 190 mm X 65 mm
(1.5in x 7.25in x 2.5in)